



685 - 1440kg Roues motrices

Capacité de charge testée selon la norme EN12532 (4km/h) et EN12533 (6km/h)

FTB, 92 Shore A	Description de l'article					Capacité de charge [kg]			Commande N°	Code EAN
						4 km/h	6 km/h			
	Corps de roue fonte peinte, clavetage selon la norme 6885, Bandage polyuréthane coulé, résistance à la température de -40°C à +60°C	125	50	17	60	780	650		FTB125x50-Ø17 H7	4031582318920
		125	50	20	60	685	570		FTB125x50-Ø20 H7	4031582318890
		125	50	25	60	685	570		FTB125x50-Ø25 H7	4031582318906
		125	50	30	60	685	570		FTB125x50-Ø30 H7	4031582318913
		160	50	17	60	925	770		FTB160x50-Ø17 H7	4031582318968
		160	50	20	60	925	770		FTB160x50-Ø20 H7	4031582318975
		160	50	25	60	925	770		FTB160x50-Ø25 H7	4031582318982
		160	50	30	60	925	770		FTB160x50-Ø30 H7	4031582318999
		200	50	20	60	1200	1000		FTB200x50-Ø20 H7	4031582319040
		200	50	25	60	1200	1000		FTB200x50-Ø25 H7	4031582319057
		200	50	30	60	1200	1000		FTB200x50-Ø30 H7	4031582319064
		200	50	35	60	1200	1000		FTB200x50-Ø35 H7	4031582319071
		250	50	20	60	1440	1200		FTB250x50-Ø20 H7	4031582319170
		250	50	25	60	1440	1200		FTB250x50-Ø25 H7	4031582319187
		250	50	30	60	1440	1200		FTB250x50-Ø30 H7	4031582319194
		250	50	35	60	1440	1200		FTB250x50-Ø35 H7	4031582319200
250	50	40	60	1440	1200		FTB250x50-Ø40 H7	4031582319217		

